


3D1



Description:	3 valves manifold – direct mounting
Descripción:	Manifold 3 valvulas – montaje directo
Description:	Manifold 3 vannes – montage direct
Connections:	Process: 1/2" NPT-F Instrument: flanged (direct mounting) Drain: 1/4" NPT-F + plug
Conexiones:	Proceso: 1/2" NPT-F Instrumento: brida (montaje directo) Purga: 1/4" NPT-F + tapon
Connections:	Process: 1/2" NPT-F Instrument: bride (montage direct) Purge: 1/4" NPT-F + bouchon
Pressure rating:	
Presion de servicio:	6000 psi
Pression:	

Material:	A105, AISI 316/L, Monel, Hastelloy, ...
Material:	
Materiaux:	
Gland Packing:	PTFE (for temperature up to 180 °C) Graphoil (for temperature over 180 °C)
Estopada:	PTFE (para temperatura hasta 180 °C) Graphoil (para temperatura mas de 180 °C)
Guarniture:	PTFE (pour temperature jusqu'à 180 °C) Graphoil (pour temperature plus de 180 °C)
Accessories (included):	Q.ty 4 7/16" UNF mounting bolts Q.ty 2 PTFE sealing ring
Accesorios (incluido):	C.tad 4 7/16" UNF bulones de montajes C.tad 2 PTFE junta de sello
Accessoires (inclus):	Q.tè 4 7/16" UNF boulon d'assemblage Q.tè 2 PTFE joints de brides

Model:
Modelo: 3D1
Modèle: