



MALE ADAPTER

AM

Metric OD tube x Male NPT thread

T TUBE OD	P NPT MALE	A	B	E	F	PART No.
3	1/4"	34.8	9.6	7.1	14	M - 3 - 4 - AM
6	1/8"	32.8	14.3	4.6	14	M - 6 - 2 - AM
6	1/4"	38.1	14.3	4.6	14	M - 6 - 4 - AM
8	1/4"	39.1	14.3	6.2	14	M - 8 - 4 - AM
10	1/4"	39.9	14.3	7.7	14	M - 10 - 4 - AM
10	3/8"	40.6	14.3	7.7	19	M - 10 - 6 - AM
12	1/4"	46.5	14.3	7.1	14	M - 12 - 4 - AM
12	3/8"	46.5	14.3	9.1	19	M - 12 - 6 - AM
12	1/2"	52.0	14.3	9.1	22	M - 12 - 8 - AM
25	3/4"	62.0	19.1	15.7	27	M - 25 - 12 - AM
25	1"	66.8	23.8	15.7	35	M - 25 - 16 - AM
30	1"	79.2	23.8	22.2	41	M - 30 - 16 - AM
30	1.1/4"	80.0	23.8	24.6	45	M - 30 - 20 - AM
32	1.1/4"	81.0	23.8	27.4	46	M - 32 - 20 - AM
38	1.1/2"	92.2	26.2	33.3	55	M - 38 - 24 - AM

Inch OD tube x Male NPT thread

T TUBE OD	P NPT MALE	A	B	E	F	PART No.
1/8"	1/8"	29.5	9.6	4.8	11	P - 2 - 2 - AM
1/8"	1/4"	34.8	14.4	7.1	14	P - 2 - 4 - AM
1/4"	1/8"	31.8	9.6	4.8	11	P - 4 - 2 - AM
1/4"	1/4"	37.0	14.3	4.8	14	P - 4 - 4 - AM
1/4"	3/8"	37.8	14.3	4.8	19	P - 4 - 6 - AM
1/4"	1/2"	43.4	19.1	4.8	22	P - 4 - 8 - AM
5/16"	1/4"	38.1	14.3	6.3	14	P - 5 - 4 - AM
3/8"	1/4"	38.9	14.3	7.1	14	P - 6 - 4 - AM
3/8"	3/8"	39.6	14.3	7.1	19	P - 6 - 6 - AM
3/8"	1/2"	45.2	19.1	7.1	22	P - 6 - 8 - AM
1/2"	1/4"	44.5	14.3	7.1	14	P - 8 - 4 - AM
1/2"	3/8"	45.2	14.3	9.9	19	P - 8 - 6 - AM
1/2"	1/2"	50.8	19.1	9.9	22	P - 8 - 8 - AM
5/8"	1/2"	52.3	19.1	11.9	22	P - 10 - 8 - AM
3/4"	1/2"	52.3	19.1	11.9	22	P - 12 - 8 - AM
3/4"	3/4"	52.3	19.1	15.0	27	P - 12 - 12 - AM
1"	3/4"	58.7	19.1	15.7	27	P - 16 - 12 - AM
1"	1"	66.0	23.8	20.3	35	P - 16 - 16 - AM
1.1/4"	1.1/4"	80.3	23.8	27.6	45	P - 20 - 20 - AM
1.1/2"	1.1/2"	94.5	26.2	33.2	55	P - 24 - 24 - AM